

In re Patent Application of:
KELVIN TODD EVANS
Serial No. **10/620,283**
Filing Date: **7/15/2003**

In the Claims:

1. (Currently Amended) A manifold comprising:

an elongate tubular body having a first longitudinal port and an opposing second longitudinal port for providing fluid flow through the body along a longitudinal axis thereof, the elongate tubular body having at least one effluent retention portion and at least one conduit portion formed therein, the conduit portion having a girth less than that of the retention portion;

wherein an inner cross-sectional area of the elongate tubular member for the at least one effluent retention portion is greater than the inner cross section area for the at least one conduit portion such that fluid entering the elongate tubular member is retained within the effluent retention portion during use of the manifold having the longitudinal axis generally horizontal;

a at least one first transverse port positioned between the first and second longitudinal ports for providing a transverse fluid flow from the at least one effluent retention portion, the first transverse port having an axis within a plane of and generally orthogonal to the longitudinal axis;

a at least one second transverse port positioned between the first transverse port and at least one of the first and second longitudinal ports for providing a second transverse fluid flow from a second retention portion of the at least one

In re Patent Application of:
KELVIN TODD EVANS
Serial No. **10/620,283**
Filing Date: **7/15/2003**

retention portion, the second transverse port having an axis within the plane of the and generally orthogonal to the longitudinal axis; and

opposing first and second ribs extending outwardly from an outside surface of the conduit portion of the tubular body, wherein the first and second ribs radially extend from the longitudinal axis and are orthogonal to the plane having the transverse port axes and longitudinal axis therein, and wherein the ribs provide means for supporting the manifold therefrom during an installation of the manifold.

2. (Previously Presented) A manifold according to claim 1, wherein each of the ports is closed, and wherein a cut is made in the manifold for opening a selected one of the ports for permitting fluid flow therethrough.

3. (Previously Presented) A manifold according to claim 1, wherein the first and second ports are centered about a longitudinal axis of the elongate tubular body.

4. (Currently Amended) A manifold according to claim 1, wherein the at least one effluent retention portion comprises three effluent retention portions, and wherein two of the three effluent retention portions each have a first transverse port extending therefrom for directing fluid flow into the a first transverse direction and the at least one second transverse port extending from the third effluent retention portion for

In re Patent Application of:

KELVIN TODD EVANS

Serial No. **10/620,283**

Filing Date: **7/15/2003**

directing flow into the a second transverse direction, which second transverse direction radially opposes the first transverse direction.

5. (Currently Amended) A manifold according to claim 4, wherein a top plan view thereof of the manifold comprises a mirror image of a bottom plan view thereof of the manifold.

6. (Currently Amended) A manifold according to claim 1, wherein the first and second longitudinal ports comprise male and female connections respectively, each for connecting to a second manifold having a similar form thereto.

7. (Currently Amended) a A manifold comprising:
an elongate tubular body having a first longitudinal port and an opposing second longitudinal port for providing fluid flow therethrough, the elongate tubular body having at least one effluent retention portion and at least one conduit portion formed therein, wherein an inner cross-sectional area of the elongate tubular member for the at least one effluent retention portion is greater than the inner cross section area for the at least one conduit portion such that fluid entering the elongate tubular member is retained within the effluent retention portion during use of the manifold having the longitudinal

In re Patent Application of:
KELVIN TODD EVANS
Serial No. **10/620,283**
Filing Date: **7/15/2003**

axis generally horizontal ~~the conduit portion having a girth less than that of the retention~~
~~portion;~~

a at least one first transverse port positioned between the first and second longitudinal ports for providing a transverse fluid flow from the elongate tubular body in a first transverse direction;

a at least one second transverse port positioned between the first and second longitudinal ports for providing a second transverse fluid flow from the elongate tubular body in a second transverse direction; and

a at least one rib extending outwardly from an outside surface of the conduit portion of the tubular body orthogonally to a plane having an axis of at least one transverse port and the longitudinal axis of the elongate tubular body therein.

8. (Previously Presented) A manifold according to claim 7, wherein each of the ports is closed, and wherein a cut is made in the manifold for opening a selected one of the ports for permitting fluid flow therethrough.

9. (Previously Presented) A manifold according to claim 7, wherein at least one of the first and second transverse ports extends from the at least one effluent retention portion.

In re Patent Application of:
KELVIN TODD EVANS
Serial No. **10/620,283**
Filing Date: **7/15/2003**

10. (Currently Amended) A manifold according to claim 7, wherein the at least one rib comprises opposing first and second ribs radially extending from the elongate tubular body along the longitudinal axis.

11. (Currently Amended) A manifold according to claim 7, wherein the first and second ports are centered about a the longitudinal axis of the elongate tubular body.

12. (Previously Presented) A manifold according to claim 11, wherein axes of the first and second transverse ports lie within a single plane of and are generally orthogonal to the longitudinal axis.

13. (Currently Amended) A manifold according to claim 7, wherein the at least one effluent retention portion comprises three effluent retention portions, and wherein two of the three effluent retention portions each have ~~the~~ a first transverse port extending therefrom for directing fluid flow into the first transverse direction and the second transverse port extending from the third effluent retention portion for directing flow into the second transverse direction, which second transverse direction radially opposes the first transverse direction.

In re Patent Application of:
KELVIN TODD EVANS
Serial No. **10/620,283**
Filing Date: **7/15/2003**

14. (Previously Presented) A manifold according to claim 13, wherein the second transverse port is positioned between the two first transverse ports.

15. (Currently Amended) A manifold according to claim 13, wherein the at least one rib comprises opposing first and second ribs radially extending from the elongate tubular body along the longitudinal axis.

16. (Currently Amended) A manifold according to claim 15, wherein a top plan view thereof of the manifold comprises a mirror image of a bottom plan view thereof of the manifold.

17. (Currently Amended) A manifold according to claim 7, wherein the first and second longitudinal ports comprise a male and a female connection respectively, each for connecting to a second manifold having a similar form thereto.

18. (Currently Amended) A manifold according to claim 7, further comprising a septic tank pipe connected to the first transverse port and a drain field field pipe connected to the second transverse port for providing fluid flow therebetween.

In re Patent Application of:
KELVIN TODD EVANS
Serial No. **10/620,283**
Filing Date: **7/15/2003**

19. (Currently Amended) A manifold comprising:

a an elongate tubular body having an input ~~port~~ portion and an opposing output ~~port~~ portion, and an ~~enlarged-girth~~ intermediate portion extending ~~at least partially~~ therebetween;

wherein an inner cross-sectional area of the elongate tubular body for the intermediate portion is greater than the inner cross sectional area of the input and output portions such that fluid entering the elongate tubular members is retained within the intermediate portion when a longitudinal axis of the tubular member is generally horizontal;

a at least one transverse port extending from the ~~enlarged-girth~~ intermediate portion; and

the transverse port positioned for permitting at least a portion of the fluid to be retained in the intermediate portion when the longitudinal axis is generally horizontal;
and

a at least one rib outwardly extending from the tubular body at a location removed from the ~~enlarged-girth~~ intermediate portion, for supporting the manifold therefrom during an installation thereof.

In re Patent Application of:
KELVIN TODD EVANS
Serial No. 10/620,283
Filing Date: 7/15/2003

20. (Currently Amended) A manifold according to claim 19, wherein ~~a~~the longitudinal axis passing through a center of the input and output ~~ports~~ports is orthogonal to a transverse axis passing through a center of the at least one transverse port.

21. (Currently Amended) A manifold according to claim 19, wherein the at least one rib comprises opposing first and second ribs radially extending from the elongate tubular body.

22. (Currently Amended) A manifold according to claim 19, wherein the at least one transverse port includes ~~at least~~ three transverse ports, and wherein a central axis for each of the ~~at least~~ three transverse ports lies ~~with~~ within a plane including ~~a central~~ the longitudinal axis of the tubular body.

23. (Currently Amended) A manifold according to claim ~~19~~22, wherein the at least one rib comprises opposing first and second ribs radially extending from the elongate tubular body.

In re Patent Application of:

KELVIN TODD EVANS

Serial No. **10/620,283**

Filing Date: **7/15/2003**

24. (New) A manifold according to claim 1, wherein the inner cross-sectional areas are circular.

25. (New) A manifold according to claim 7, wherein the inner cross-sectional areas are circular.

26. (New) A manifold comprising:

an elongate tubular body having a first longitudinal port and an opposing second longitudinal port for providing fluid flow through the body along a longitudinal axis thereof, the elongate tubular body having at least one effluent retention portion and at least one conduit portion formed therein, wherein an inner cross-sectional area of the elongate tubular member for the at least one effluent retention portion is greater than the inner cross section area for the at least one conduit portion such that fluid entering the elongate tubular member is retained within the effluent retention portion during use of the manifold having the longitudinal axis generally horizontal;

at least one first transverse port positioned between the first and second longitudinal ports for providing a transverse fluid flow from the at least one effluent retention portion, the first transverse port having an axis within a plane of and generally orthogonal to the longitudinal axis; and

In re Patent Application of:
KELVIN TODD EVANS
Serial No. **10/620,283**
Filing Date: **7/15/2003**

at least one second transverse port positioned between the first transverse port and at least one of the first and second longitudinal ports for providing a second transverse fluid flow from a second retention portion of the at least one retention portion, the second transverse port having an axis within the plane of the and generally orthogonal to the longitudinal axis.

27. (New) A manifold according to claim 26, further comprising opposing first and second ribs extending outwardly from an outside surface of the conduit portion of the tubular body, wherein the first and second ribs radially extend from the longitudinal axis and are orthogonal to the plane having the transverse port axes and longitudinal axis therein, and wherein the ribs provide means for supporting the manifold therefrom during an installation of the manifold.

28. (New) A manifold according to claim 26, wherein each of the ports is closed, and wherein a cut is made in the manifold for opening a selected one of the ports for permitting fluid flow therethrough.

29. (New) A manifold according to claim 26, wherein the first and second ports are centered about a longitudinal axis of the elongate tubular body.

In re Patent Application of:
KELVIN TODD EVANS
Serial No. **10/620,283**
Filing Date: **7/15/2003**

30. (New) A manifold according to claim 26, wherein the at least one effluent retention portion comprises three effluent retention portions, and wherein two of the three effluent retention portions each have the a first transverse port extending therefrom for directing fluid flow into a first transverse direction and the at least one second transverse port extending from the third effluent retention portion for directing flow into a second transverse direction, which second transverse direction radially opposes the first transverse direction.

31. (New) A manifold according to claim 30, wherein a top plan view of the manifold comprises a mirror image of a bottom plan view of the manifold.

32. (New) A manifold according to claim 26, wherein the first and second longitudinal ports comprise male and female connections respectively, each for connecting to a second manifold having a similar form thereto.

33. (New) A manifold according to claim 26, wherein the inner cross-sectional areas are circular.